

Sites Imported Aggregate Briefing

September 9, 2022

Agenda

- Project Description
- Dam Filter, Drain and Transition Zones
- Road Base
- Concrete Aggregate
- Summary of Quantities
- Questions

Project Description

Project Location

80 miles north of Sacramento

10 miles west of Maxwell

45 miles south of Orland




Sites Reservoir Features

Total Storage Capacity	1.5 MAF
Active Storage Capacity	1.4 MAF
Approximate Inundation Area	13,200 acres
Approximate Watershed Area	54,150 acres (84.6 mi ²)
Dam/Saddle Dam/Dike Crest Elevation (Without Camber)	517 feet
Dam Heights (approx. - max. ht. above streambed): Golden Gate Dam Sites Dam 7 Saddle Dams*/2 Saddle Dikes (for freeboard)	287 feet 267 feet 12 – 107 feet
Maximum Operating Water Elevation	498 feet
Minimum Operating Water Elevation	340 feet
Top of Dead Pool	300 feet
Inlet/Outlet Facilities:	
I/O Tunnel (single), with sloping intake (south of GG Dam)	32 feet ID
Sites Diversion Tunnel (north abutment of Sites Dam)	12 feet ID


* Saddle Dam 8B is the spillway location.

Sites Reservoir Features – Construction




Dam Filter, Drain and Transition Zones

Golden Gate Dam




Typical Golden Gate and Sites Dam Section



Material Balance Golden Gate Dam

MATERIALS BALANCE GOLDEN GATE DAM - 1.5 MAF RESERVOIR

Calculated by: EN
Reviewed by: MS
Date: January, 2021



Examples of Dam Construction



Examples of Dam Construction



Examples of Dam Construction



Examples of Dam Construction




Examples of Filter Gradations and Requirements

Generally meet the soundness requirements of ASTM C33 for fine aggregate plus requirements below

Test Type	Acceptability Standard	Criteria
Specific Gravity	ASTM C127	Greater than 2.6
Abrasion Resistance	ASTM C131	10 percent maximum loss by weight at 100 revolutions, and 40 percent loss of weight at 500 revolutions
	ASTM C535	40 percent maximum loss of weight at 1000 revolutions
Sodium Sulfate Soundness	ASTM C88	10 percent maximum weighted average loss by weight, after five cycles
Shape		Particles shall be generally equidimensional
Elongated Particles	CRD-C-119 and CRD-C-120	Not greater than 15 percent by weight
Other		Material shall be free of clay balls, organics, soft particles, and other impurities

Examples of Filter Gradations and Requirements




Note: No gap or skip grading between any two consecutive sieves

Sieve Size	Calaveras	Diamond Valley	Los Vaqueros
3/8-inch	100	100	100
No. 4	95 – 100	90 – 100	95 – 100
No. 8	65 – 95	75 – 90	80 – 100
No. 16	40 – 65	50 – 70	50 – 85
No. 30	20 – 45	25 – 45	25 – 60
No. 50	5 – 25	3 – 15	10 – 30
No. 100	0 – 10	0 – 2	2 – 10
No. 200	0 – 4	-	0 – 4

Examples of Drain Gradations and Requirements

Test Type	Acceptability Standard	Criteria
Adsorption	ASTM C127	Greater than 2.6
Specific Gravity	ASTM C127 and C128	Greater than 2.6
Abrasion Resistance	ASTM C131	10 percent maximum loss by weight at 100 revolutions, and 40 percent loss of weight at 500 revolutions
Sodium Sulfate Soundness	ASTM C88	10 percent maximum weighted average loss by weight, after five cycles
Shape		Particles shall be generally equidimensional
Elongated Particles	CRD-C-119 and CRD-C-120	Not greater than 15 percent by weight
Other		Material shall be free of clay balls, organics, soft particles, and other impurities

Examples of Drain Gradations and Requirements




Note: No gap or skip grading between any two consecutive sieves

Sieve Size	Calaveras	Diamond Valley	Los Vaqueros
1.5-inch	-	100	100
1-inch	100	60 – 100	-
3/4-inch	85 – 100	50 – 85	75 – 100
3/8-inch	30 – 98	25 – 55	50 – 80
No. 4	5 – 45	3 – 15	20 – 50
No. 8	0 – 5	0 – 2	2 – 20
No. 16	-	-	0 – 3
No. 200	0 – 3	-	-

Examples of Transition Gradations and Requirements

- Similar soundness requirements to filter and drain



Sieve Size	Calaveras (Upstream)	Calaveras (Downstream)	Diamond Valley (Upstream)	Diamond Valley (Downstream)
6-inch	-	-	-	100
4-inch	-	100	-	-
3-inch	-	70 – 100	-	60 – 100
1.5-inch	-	40 – 90	100	-
1-inch	-	20 – 60	-	20 – 40
¾-inch	100	-	80 – 100	-
3/8-inch	75 – 100	0 – 30	60 – 85	0 – 10
No. 4	60 – 80	0 – 10	50 – 75	0 – 5
No. 16	30 – 55	-	30 – 50	-
No. 50	5 – 30	-	10 – 30	-
No. 200	0 – 4	-	0 – 3	-


Road Base

Road Base

- Caltrans Class 2 Aggregate Base (standard specifications 26-1.02)
 - Consists of clean broken stone, crushed gravel, natural rough-surfaces gravel, sand, and/or processed reclaimed AC, PCC, LCB, or CTB


Sieve size	Percentage passing			
	1-1/2 inch maximum		3/4 inch maximum	
	Operating range	Contract compliance	Operating range	Contract compliance
2"	100	100	--	--
1-1/2"	90-100	87-100	--	--
1"	--	--	100	100
3/4"	50-85	45-90	90-100	87-100
No. 4	25-45	20-50	35-60	30-65
No. 30	10-25	6-29	10-30	5-35
No. 200	2-9	0-12	2-9	0-12

Quality characteristic	Requirement	
	Operating range	Contract compliance
Resistance (R-value, min)	--	78
Sand equivalent (min)	25	22
Durability index (min)	--	35



Road Base

- Caltrans Class 4 Aggregate Subbase (standard specifications 25-1.02)
 - Consists of clean broken stone, crushed gravel, natural rough-surfaces gravel, sand, and/or processed reclaimed AC, PCC, LCB, or CTB
 - Gradation and quality requirements to be decided based on project needs, but likely to have a minimum sand equivalent of about 20 and R-value of about 40



Concrete Aggregate

Concrete Aggregate

- Need to meet quality requirements of ASTM C33, Concrete Aggregates

Location	Approximate Quantities (tons)
Spillway (Saddle Dam 8B)	19,500
Inlet/Outlet Structure	115,900
Sites Diversion Tunnel	10,400
Golden Gate Dam Bypass	35,000
Sites Lodoga Bridge	45,585

Summary of Quantities

Summary of Quantities

Location	Approximate Quantities (Million Tons)
Zone 2A – Downstream Filter	1.5
Zone 2A – Downstream Drain	1.6
Zone 2A – Downstream Transition	0.3
Zone 2B – Upstream Filter	0.6
Zone 2B – Upstream Transition	0.6
Class 4 Aggregate Subbase	0.3
Class 2 Aggregate Base	0.5
Concrete Aggregate	0.6
Total	6.0 million tons

Crude Average Delivery Schedule

- **Overall Project Schedule = 800 to 1200 days**
- **Overall Quantity of Material = 6 million tons**
- **Average Delivery = 6,000 to 7,500 tons per day**

Questions



Questions

- Do you have the quality of materials needed and their location(s)?
- Do you have the plants to create the materials in spec and their location(s)?
- Do you have the capacity to deliver the quality and quantities of materials in the time needed?

Questions – cont'd.

- Do you have technical specifications/lab certifications such as durability, gradation, petrographic analysis, LA rattler, R-value, available?
- What is the location of quarry and type of material; alluvium, hard rock, soft rock?
- What are the available material remaining/duration of permitted operations?

Questions – cont'd.

- What are the productivity rates for different materials?
- What is the maximum amount of material you can deliver per day?
- What are the approximate at plant costs for different materials?
- Will you be using prevailing labor rates for trucking?